

# OpcClientApplication Class

**Namespace:** Opc.UaFx.Client

**Assemblies:** Opc.UaFx.Advanced.dll

**C#**

```
[CLSCompliant(false)]
public class OpcClientApplication : OpcClientApplication<OpcClient>, IOpcApplication,
IDisposable
```

**Inheritance** [Object](#) > [OpcApplication](#) > [OpcClientApplication<OpcClient>](#) > [OpcClientApplication](#)

**Attributes** [CLSCompliantAttribute](#)

**Implements** [IOpcApplication](#), [IDisposable](#)

## Constructors

Name	Description
<a href="#">OpcClientApplication(OpcClient)</a>	
<a href="#">OpcClientApplication(String)</a>	
<a href="#">OpcClientApplication(Uri)</a>	

## Events

Name	Description
<a href="#">Exited</a>	(Inherited from <a href="#">OpcApplication</a> )
<a href="#">Exiting</a>	(Inherited from <a href="#">OpcApplication</a> )
<a href="#">Started</a>	(Inherited from <a href="#">OpcApplication</a> )
<a href="#">Starting</a>	(Inherited from <a href="#">OpcApplication</a> )

## Properties

Name	Description
<a href="#">Company</a>	(Inherited from <a href="#">OpcApplication</a> )
<a href="#">Configuration</a>	(Inherited from <a href="#">OpcApplication</a> )
<a href="#">Current</a>	(Inherited from <a href="#">OpcApplication</a> )
<a href="#">Name</a>	(Inherited from <a href="#">OpcApplication</a> )
<a href="#">ProductCompany</a>	(Inherited from <a href="#">OpcApplication</a> )
<a href="#">ProductName</a>	(Inherited from <a href="#">OpcApplication</a> )
<a href="#">ProductVersion</a>	(Inherited from <a href="#">OpcApplication</a> )
<a href="#">Version</a>	(Inherited from <a href="#">OpcApplication</a> )

# Methods

Name	Description
AfterRun	(Inherited from <a href="#">OpcApplication</a> )
BeforeRun	(Inherited from <a href="#">OpcApplication</a> )
Dispose	Releases all resources used by the <a href="#">OpcApplication</a> . (Inherited from <a href="#">OpcApplication</a> )
Dispose(Boolean)	Releases the unmanaged resources used by the <a href="#">OpcApplication</a> and optionally releases the managed resources. (Inherited from <a href="#">OpcApplication</a> )
Exit	(Inherited from <a href="#">OpcApplication</a> )
ExitCore	(Inherited from <a href="#">OpcApplication</a> )
LoadConfiguration	(Inherited from <a href="#">OpcApplication</a> )
LoadConfiguration(String)	(Inherited from <a href="#">OpcApplication</a> )
LoadConfigurationCore(String)	(Inherited from <a href="#">OpcApplication</a> )
OnExited(EventArgs)	(Inherited from <a href="#">OpcApplication</a> )
OnExiting(EventArgs)	(Inherited from <a href="#">OpcApplication</a> )
OnStarted(EventArgs)	(Inherited from <a href="#">OpcApplication</a> )
OnStarting(EventArgs)	(Inherited from <a href="#">OpcApplication</a> )
Run	(Inherited from <a href="#">OpcApplication</a> )
RunCore	(Inherited from <a href="#">OpcApplication</a> )

# Table of Contents

<b>Constructors</b>	1
<b>Events</b>	1
<b>Properties</b>	1
<b>Methods</b>	2

