

# OpcDataItemNode Class

**Namespace:** Opc.UaFx

**Assemblies:** Opc.UaFx.Advanced.dll

Defines a specialisation of the [OpcDataVariableNode](#) which defines the general characteristics of a data item.

**C#**

```
public class OpcDataItemNode : OpcDataVariableNode, IOpcNode, IOpcNodeInfo
```

**Inheritance** [Object](#) > [OpcNode](#) > [OpcInstanceNode](#) > [OpcVariableNode](#) > [OpcDataVariableNode](#) > [OpcDataItemNode](#)

## Derived

- [OpcAnalogItemNode](#)
- [OpcDataItemNode`1](#)

**Implements** [IOpcNode](#), [IOpcNodeInfo](#)

## Constructors

Name	Description
<a href="#">OpcDataItemNode</a> ( <a href="#">IOpcNode</a> , <a href="#">OpcName</a> )	Initializes a new instance of the <a href="#">OpcDataItemNode</a> class accessible by the <a href="#">name</a> specified as a child node of the <a href="#">parent</a> node given.
<a href="#">OpcDataItemNode</a> ( <a href="#">IOpcNode</a> , <a href="#">OpcName</a> , <a href="#">Object</a> )	Initializes a new instance of the <a href="#">OpcDataItemNode</a> class accessible by the <a href="#">name</a> specified with the initial value defined by <a href="#">value</a> as a child node of the <a href="#">parent</a> node given.
<a href="#">OpcDataItemNode</a> ( <a href="#">IOpcNode</a> , <a href="#">OpcName</a> , <a href="#">OpcNodeId</a> )	Initializes a new instance of the <a href="#">OpcDataItemNode</a> class accessible by the <a href="#">name</a> and <a href="#">id</a> specified as a child node of the <a href="#">parent</a> node given.
<a href="#">OpcDataItemNode</a> ( <a href="#">IOpcNode</a> , <a href="#">OpcName</a> , <a href="#">OpcNodeId</a> , <a href="#">Object</a> )	Initializes a new instance of the <a href="#">OpcDataItemNode</a> class accessible by the <a href="#">name</a> and <a href="#">id</a> specified with the initial value defined by <a href="#">value</a> as a child node of the <a href="#">parent</a> node given.
<a href="#">OpcDataItemNode</a> ( <a href="#">OpcName</a> )	Initializes a new instance of the <a href="#">OpcDataItemNode</a> class accessible by the <a href="#">name</a> specified.
<a href="#">OpcDataItemNode</a> ( <a href="#">OpcName</a> , <a href="#">Object</a> )	Initializes a new instance of the <a href="#">OpcDataItemNode</a> class accessible by the <a href="#">name</a> specified with the initial value given by <a href="#">value</a> .
<a href="#">OpcDataItemNode</a> ( <a href="#">OpcName</a> , <a href="#">OpcNodeId</a> )	Initializes a new instance of the <a href="#">OpcDataItemNode</a> class accessible by the <a href="#">name</a> and <a href="#">id</a> specified.
<a href="#">OpcDataItemNode</a> ( <a href="#">OpcName</a> , <a href="#">OpcNodeId</a> , <a href="#">Object</a> )	Initializes a new instance of the <a href="#">OpcDataItemNode</a> class accessible by the <a href="#">name</a> and <a href="#">id</a> specified with the initial value given by <a href="#">value</a> .

# Events

Name	Description
AfterApplyChanges	Occurs after one or more changes on the node has been notified. (Inherited from <a href="#">OpcNode</a> )
BeforeApplyChanges	Occurs before one or more changes on the node are notified. (Inherited from <a href="#">OpcNode</a> )

# Properties

Name	Description
<a href="#">AccessLevel</a>	Gets or sets a value which indicates in which ways the <a href="#">Value</a> attribute of the variable node can be accessed (read/write) and if it provides current and/or historic data. (Inherited from <a href="#">OpcVariableNode</a> )
<a href="#">ArrayDimensions</a>	Gets the number/lengths of dimensions for an array <a href="#">Value</a> with one or more fixed dimensions. (Inherited from <a href="#">OpcVariableNode</a> )
<a href="#">Category</a>	Gets the <a href="#">NodeCategoryOpcAttribute</a> which identifies the kind of node and is therefore used to classify the node regarding its use and purpose. (Inherited from <a href="#">OpcNode</a> )
<a href="#">DataType</a>	Gets or sets a value which defines a pre-defined used <a href="#">DataTypeId</a> as one of the members defined by the <a href="#">OpcDataType</a> enumeration to simplify querying standard data types. (Inherited from <a href="#">OpcVariableNode</a> )
<a href="#">DataTypeId</a>	Gets or sets the identifier which identifies the node that defines the type of data represented by the variable node. (Inherited from <a href="#">OpcVariableNode</a> )
<a href="#">DefaultReferenceTypeId</a>	Gets the default identifier which identifies the type that defines the underlying node reference within this <a href="#">OpcInstanceNode</a> is referenced by its parent node. (Inherited from <a href="#">OpcInstanceNode</a> )
<a href="#">DefaultReferenceTypeId</a>	Gets the default identifier which identifies the type that defines the underlying node reference within this <a href="#">OpcInstanceNode</a> is referenced by its parent node. (Inherited from <a href="#">OpcVariableNode</a> )
<a href="#">DefaultTypeDefinitionId</a>	Gets the default identifier which identifies the node that defines the underlying node type from that this <a href="#">OpcInstanceNode</a> has been created.
<a href="#">DefaultTypeDefinitionId</a>	Gets the default identifier which identifies the node that defines the underlying node type from that this <a href="#">OpcInstanceNode</a> has been created. (Inherited from <a href="#">OpcInstanceNode</a> )
<a href="#">DefaultTypeDefinitionId</a>	Gets the default identifier which identifies the node that defines the underlying node type from that this <a href="#">OpcInstanceNode</a> has been created. (Inherited from <a href="#">OpcVariableNode</a> )
<a href="#">DefaultTypeDefinitionId</a>	Gets the default identifier which identifies the node that defines the underlying node type from that this <a href="#">OpcInstanceNode</a> has been created. (Inherited from <a href="#">OpcDataVariableNode</a> )
<a href="#">Definition</a>	Gets or sets a vendor-specific, human readable string that specifies how the value of this data item is calculated.
<a href="#">DefinitionNode</a>	Gets the <a href="#">OpcPropertyNode</a> '1 of the <a href="#">Definition</a> property.
<a href="#">Description</a>	Gets or sets the value of the optional <a href="#">DescriptionOpcAttribute</a> which shall explain the meaning of the node. (Inherited from <a href="#">OpcNode</a> )

Name	Description
Descriptions	Gets the <a href="#">OpcNodeGlobalization</a> instance used to control the localization and other globalization related tasks for the <a href="#">Description</a> attribute of the current node. (Inherited from <a href="#">OpcNode</a> )
DisplayName	Gets or sets the value of the <a href="#">DisplayNameOpcAttribute</a> which defines the localizable name of the node. (Inherited from <a href="#">OpcNode</a> )
DisplayNames	Gets the <a href="#">OpcNodeGlobalization</a> instance used to control the localization and other globalization related tasks for the <a href="#">DisplayName</a> attribute of the current node. (Inherited from <a href="#">OpcNode</a> )
HasPendingChanges	Gets a value indicating whether there exists any pending change on the node. (Inherited from <a href="#">OpcNode</a> )
HistoryConfiguration	(Inherited from <a href="#">OpcVariableNode</a> )
Id	Gets the value of the <a href="#">NodeIdOpcAttribute</a> which unambiguously identifies the node. (Inherited from <a href="#">OpcNode</a> )
IsArray	Gets a value indicating whether the <a href="#">Value</a> of the <a href="#">OpcVariableNode</a> represented is an array. (Inherited from <a href="#">OpcVariableNode</a> )
IsHistorizing	(Inherited from <a href="#">OpcVariableNode</a> )
ModellingRuleId	Gets or sets the identifier which defines how the <a href="#">OpcInstanceNode</a> is used for instantiation. (Inherited from <a href="#">OpcInstanceNode</a> )
Name	Gets or sets the value of the <a href="#">BrowseNameOpcAttribute</a> which defines the non-localizable human-readable name used when browsing the address space. (Inherited from <a href="#">OpcNode</a> )
Namespace	(Inherited from <a href="#">OpcNode</a> )
Parent	Gets the parent node of the node. (Inherited from <a href="#">OpcNode</a> )
Parent	Gets the parent node of the node. (Inherited from <a href="#">OpcInstanceNode</a> )
PendingChanges	Gets a value indicating the most recent changes performed on the node since their last notification. (Inherited from <a href="#">OpcNode</a> )
QueryEventsCallback	Gets or sets a callback used to query any event information which belongs to the node. (Inherited from <a href="#">OpcNode</a> )
ReadAccessLevelCallback	(Inherited from <a href="#">OpcVariableNode</a> )
ReadArrayDimensionsCallback	(Inherited from <a href="#">OpcVariableNode</a> )
ReadDataTypeCallback	(Inherited from <a href="#">OpcVariableNode</a> )
ReadDescriptionCallback	(Inherited from <a href="#">OpcNode</a> )
ReadDisplayNameCallback	(Inherited from <a href="#">OpcNode</a> )
ReadIsHistorizingCallback	(Inherited from <a href="#">OpcVariableNode</a> )
ReadUserAccessLevelCallback	(Inherited from <a href="#">OpcVariableNode</a> )
ReadUserWriteAccessCallback	(Inherited from <a href="#">OpcNode</a> )
ReadValueRankCallback	(Inherited from <a href="#">OpcVariableNode</a> )
ReadVariableValueCallback	Gets or sets a callback used to read the variable value. (Inherited from <a href="#">OpcVariableNode</a> )
ReadWriteAccessCallback	(Inherited from <a href="#">OpcNode</a> )

Name	Description
ReferenceType	Gets a value which defines a pre-defined used <a href="#">ReferenceTypeId</a> as one of the members defined by the <a href="#">OpcReferenceType</a> enumeration to simplify querying standard reference types. (Inherited from <a href="#">OpcInstanceNode</a> )
ReferenceTypeId	Gets or sets the identifier which identifies the node that defines the semantic of the reference between a source and a target node and generally reflects an operation between the two, such as "A contains B". (Inherited from <a href="#">OpcInstanceNode</a> )
Status	(Inherited from <a href="#">OpcVariableNode</a> )
SymbolicName	(Inherited from <a href="#">OpcNode</a> )
Tag	Gets or sets the object that contains additional user data about the node. (Inherited from <a href="#">OpcNode</a> )
Timestamp	(Inherited from <a href="#">OpcVariableNode</a> )
TypeDefinitionId	Gets or sets the identifier which identifies the node that defines the underlying node type from that this <a href="#">OpcInstanceNode</a> has been created. (Inherited from <a href="#">OpcInstanceNode</a> )
UserAccessLevel	Gets or sets a value which indicates in which ways the <a href="#">Value</a> attribute of the variable node can be accessed (read/write) and if it provides current and/or historic data taking user access rights into account. (Inherited from <a href="#">OpcVariableNode</a> )
UserWriteAccess	Gets or sets the value of the optional <a href="#">UserWriteAccessOpcAttribute</a> which exposes the possibilities of a client to write the attributes of the node taking user access rights into account. (Inherited from <a href="#">OpcNode</a> )
Value	Gets or sets the value of the variable node which may be simple or complex. (Inherited from <a href="#">OpcVariableNode</a> )
ValuePrecision	Gets or sets a value which specifies the maximum precision that the server can maintain for the item based on restrictions in the target environment.
ValuePrecisionNode	Gets the <a href="#">OpcPropertyNode</a> '1 of the <a href="#">ValuePrecision</a> property.
ValueRank	(Inherited from <a href="#">OpcVariableNode</a> )
WriteAccess	Gets or sets the value of the optional <a href="#">WriteAccessOpcAttribute</a> which exposes the possibilities of a client to write the attributes of the node. (Inherited from <a href="#">OpcNode</a> )
WriteAccessLevelCallback	(Inherited from <a href="#">OpcVariableNode</a> )
WriteArrayDimensionsCallback	(Inherited from <a href="#">OpcVariableNode</a> )
WriteDataTypeCallback	(Inherited from <a href="#">OpcVariableNode</a> )
WriteDescriptionCallback	(Inherited from <a href="#">OpcNode</a> )
WriteDisplayNameCallback	(Inherited from <a href="#">OpcNode</a> )
WriteIsHistorizingCallback	(Inherited from <a href="#">OpcVariableNode</a> )
WriteUserAccessLevelCallback	(Inherited from <a href="#">OpcVariableNode</a> )
WriteUserWriteAccessCallback	(Inherited from <a href="#">OpcNode</a> )
WriteValueRankCallback	(Inherited from <a href="#">OpcVariableNode</a> )
WriteVariableValueCallback	Gets or sets a callback used to write the variable value. (Inherited from <a href="#">OpcVariableNode</a> )
WriteWriteAccessCallback	(Inherited from <a href="#">OpcNode</a> )

# Methods

Name	Description
AddChild(OpcContext, OpcInstanceNode)	(Inherited from <a href="#">OpcInstanceNode</a> )
AddNotifier(OpcContext, IOpcNode)	(Inherited from <a href="#">OpcNode</a> )
ApplyChanges(OpcContext)	Notifies about changes performed on the node since the last notification and resets the pending changes to <a href="#">None</a> . (Inherited from <a href="#">OpcNode</a> )
ApplyChanges(OpcContext, Boolean)	Notifies about changes performed on the node (and optionally on its children) since the last notification and resets the pending changes to <a href="#">None</a> . (Inherited from <a href="#">OpcNode</a> )
AttributeValue(OpcAttribute)	Retrieves the value of the <a href="#">attribute</a> specified. (Inherited from <a href="#">OpcNode</a> )
AttributeValue`1(OpcAttribute)	Retrieves the value of the <a href="#">attribute</a> specified. (Inherited from <a href="#">OpcNode</a> )
Child(OpcContext, OpcName)	Retrieves the child node its <a href="#">Name</a> property matches exactly the <a href="#">name</a> specified. (Inherited from <a href="#">OpcNode</a> )
Children(OpcContext)	Retrieves a sequence of all nodes organized as children of this node. (Inherited from <a href="#">OpcNode</a> )
InitializeDefaults	Initializes the default values used by the <a href="#">OpcDataItemNode</a> .
InitializeDefaults	Initializes the default values used by the node implementation represented / required. (Inherited from <a href="#">OpcNode</a> )
InitializeDefaults	Initializes the default values used by the <a href="#">OpcInstanceNode</a> . (Inherited from <a href="#">OpcInstanceNode</a> )
InitializeDefaults	Initializes the default values used by the <a href="#">OpcVariableNode</a> . (Inherited from <a href="#">OpcVariableNode</a> )
IsChangePending(OpcNodeChanges)	(Inherited from <a href="#">OpcNode</a> )
OnAfterApplyChanges(OpcNodeChangesEventArgs)	Raises the <a href="#">AfterApplyChanges</a> event using the event data specified. (Inherited from <a href="#">OpcNode</a> )
OnBeforeApplyChanges(OpcNodeChangesEventArgs)	Raises the <a href="#">BeforeApplyChanges</a> event using the event data specified. (Inherited from <a href="#">OpcNode</a> )
QueryEventsCore(OpcNodeContext, OpcEventCollection)	(Inherited from <a href="#">OpcNode</a> )
ReadAttributeValueCore`1(OpcReadAttributeValueContext, OpcAttribute)	(Inherited from <a href="#">OpcNode</a> )

Name	Description
ReadAttributeValueCore`1(OpcReadAttributeValueContext, OpcAttributeValue)	(Inherited from OpcVariableNode)
ReadValue(OpcReadVariableValueContext)	Reads the variable node value using the <b>context</b> specified. (Inherited from OpcVariableNode)
ReadVariableValue(OpcReadVariableValueContext)	(Inherited from OpcVariableNode)
ReadVariableValueCore(OpcReadVariableValueContext, OpcVariableValue)	Reads the value of the variable node using the <b>context</b> and <b>value</b> information specified. (Inherited from OpcVariableNode)
RemoveChild(OpcContext, OpcInstanceNode)	(Inherited from OpcInstanceNode)
RemoveNotifier(OpcContext, IOpcNode)	(Inherited from OpcNode)
RemoveNotifier(OpcContext, IOpcNode)	(Inherited from OpcInstanceNode)
ReportEvent(OpcContext, OpcEvent)	(Inherited from OpcNode)
UpdateChanges(OpcContext, OpcNodeChanges)	Notifies about the <b>changes</b> on behalf of the node and removes pending changes which intersect with the <b>changes</b> specified. (Inherited from OpcNode)
UpdateChanges(OpcContext, OpcNodeChanges, Boolean)	Notifies about the <b>changes</b> on behalf of the node (and optionally on its children) and removes pending changes which intersect with the <b>changes</b> specified. (Inherited from OpcNode)
WriteAttributeValueCore`1(OpcWriteAttributeValueContext, OpcAttributeValue)	(Inherited from OpcNode)
WriteAttributeValueCore`1(OpcWriteAttributeValueContext, OpcAttributeValue)	(Inherited from OpcVariableNode)
WriteValue(OpcWriteVariableValueContext, Object)	Writes the <b>value</b> to the variable node value using the <b>context</b> specified. (Inherited from OpcVariableNode)
WriteVariableValue(OpcWriteVariableValueContext, OpcVariableValue)	(Inherited from OpcVariableNode)
WriteVariableValueCore(OpcWriteVariableValueContext, OpcVariableValue)	Writes the value of the variable node using the <b>context</b> and <b>value</b> information specified. (Inherited from OpcVariableNode)

# Table of Contents

<b>Constructors</b>	1
<b>Events</b>	2
<b>Properties</b>	2
<b>Methods</b>	5

