

OpcMethodContext Class

Namespace: Opc.UaFx

Assemblies: Opc.UaFx.Advanced.dll

Provides information and services about the system which belong to the current method call situation.

C#

```
public class OpcMethodContext : OpcNodeContext<OpcMethodNode>, IOpcNamespaceResolver
```

Inheritance [Object](#) > [OpcContext](#) > [OpcNodeContext<OpcMethodNode>](#) > [OpcMethodContext](#)

Implements [IOpcNamespaceResolver](#)

Properties

| Name | Description |
|----------------------------------|--|
| Empty | Gets an empty OpcContext which can be used in cases there a session nor system specific context is not necessarily required. (Inherited from OpcContext) |
| Identity | Gets the OpcUserIdentity which belongs to the situation represented. (Inherited from OpcContext) |
| Namespaces | Gets a read-only collection of namespaces valid in the current OpcContext . (Inherited from OpcContext) |
| NodeIdFactory | Gets the OpcNodeIdFactory used to create new node identifiers using this context. (Inherited from OpcContext) |
| Owner | Gets the owner of the current OpcContext . (Inherited from OpcContext) |
| PreferredLocales | Gets a collection of preferred locales (see CultureInfo.Name) to use to localize data and information. (Inherited from OpcContext) |
| Result | Gets or sets the OpcResult determining the outcome of the callback routine. |
| SessionId | Gets the session identifier which identifies the session within that the context has been created and is valid. (Inherited from OpcContext) |
| Target | Gets the target Object to that the method call does belong. |

Table of Contents

Properties 1