

OpcDiscoveryServer Members

Namespace: Opc.UaFx.Server

Assemblies: Opc.UaFx.Advanced.dll, Opc.UaFx.Advanced.dll

The [OpcDiscoveryServer](#) type exposes the following members.

Constructors

OpcDiscoveryServer()

C#

```
public OpcDiscoveryServer()
```

OpcDiscoveryServer(String)

C#

```
public OpcDiscoveryServer(string address)
```

Parameters

address [String](#)

Exceptions

[ArgumentException](#)

[ArgumentNullException](#)

[UriFormatException](#)

OpcDiscoveryServer(Uri)

C#

```
public OpcDiscoveryServer(Uri address)
```

Parameters

address [Uri](#)

Exceptions

[ArgumentNullException](#)

Properties

SystemContext

Gets the [OpcContext](#) which is used to store the context sensitive data and configuration used by the current [OpcDiscoveryServer](#) instance.

C#

```
public override OpcContext SystemContext { get; }
```

Property Value

[OpcContext](#)

An instance of the [OpcContext](#) class which might be at least [Empty](#).

Methods

CreateConfiguration()

C#

```
[CLSCompliant(false)]  
protected override OpcApplicationConfiguration CreateConfiguration()
```

Returns

[OpcApplicationConfiguration](#)

StartCore(OpcApplicationConfiguration)

C#

```
[CLSCompliant(false)]  
protected override void StartCore(OpcApplicationConfiguration configuration)
```

Parameters

configuration [OpcApplicationConfiguration](#)

StopCore()

C#

```
protected override void StopCore()
```


Table of Contents

Constructors	1
OpcDiscoveryServer()	1
OpcDiscoveryServer(String)	1
OpcDiscoveryServer(Uri)	1
Properties	2
SystemContext	2
Methods	2
CreateConfiguration()	2
StartCore(OpcApplicationConfiguration)	2
StopCore()	3