

# OpcOperationContext Class

**Namespace:** Opc.UaFx.Server

**Assemblies:** Opc.UaFx.Advanced.dll

**C#**

```
public class OpcOperationContext : OpcContext, IOpcNamespaceResolver
```

**Inheritance** [Object](#) > [OpcContext](#) > OpcOperationContext

**Implements** [IOpcNamespaceResolver](#)

## Properties

| Name                              | Description                                                                                                                                                                                  |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">ClientID</a>          |                                                                                                                                                                                              |
| <a href="#">Empty</a>             | Gets an empty <a href="#">OpcContext</a> which can be used in cases there a session nor system specific context is not necessarily required.<br>(Inherited from <a href="#">OpcContext</a> ) |
| <a href="#">Endpoint</a>          |                                                                                                                                                                                              |
| <a href="#">Identity</a>          | Gets the <a href="#">OpcUserIdentity</a> which belongs to the situation represented.<br>(Inherited from <a href="#">OpcContext</a> )                                                         |
| <a href="#">Namespaces</a>        | Gets a read-only collection of namespaces valid in the current <a href="#">OpcContext</a> .<br>(Inherited from <a href="#">OpcContext</a> )                                                  |
| <a href="#">NodeIdFactory</a>     | Gets the <a href="#">OpcNodeIdFactory</a> used to create new node identifiers using this context.<br>(Inherited from <a href="#">OpcContext</a> )                                            |
| <a href="#">OperationDeadline</a> |                                                                                                                                                                                              |
| <a href="#">OperationStatus</a>   |                                                                                                                                                                                              |
| <a href="#">Owner</a>             | Gets the owner of the current <a href="#">OpcContext</a> .<br>(Inherited from <a href="#">OpcContext</a> )                                                                                   |
| <a href="#">PreferredLocales</a>  | Gets a collection of preferred locales (see <a href="#">CultureInfo.Name</a> ) to use to localize data and information.                                                                      |
| <a href="#">PreferredLocales</a>  | Gets a collection of preferred locales (see <a href="#">CultureInfo.Name</a> ) to use to localize data and information.<br>(Inherited from <a href="#">OpcContext</a> )                      |
| <a href="#">RequestId</a>         |                                                                                                                                                                                              |
| <a href="#">RequestType</a>       |                                                                                                                                                                                              |
| <a href="#">Session</a>           |                                                                                                                                                                                              |
| <a href="#">SessionId</a>         |                                                                                                                                                                                              |
| <a href="#">SessionId</a>         | Gets the session identifier which identifies the session within that the context has been created and is valid.<br>(Inherited from <a href="#">OpcContext</a> )                              |
| <a href="#">Socket</a>            |                                                                                                                                                                                              |



# Table of Contents

|                   |   |
|-------------------|---|
| <b>Properties</b> | 1 |
|-------------------|---|