

OpcReadNodesHistoryRequest Members

Namespace: Opc.UaFx.Services

Assemblies: Opc.UaFx.Advanced.dll, Opc.UaFx.Advanced.dll

The [OpcReadNodesHistoryRequest](#) type exposes the following members.

Constructors

OpcReadNodesHistoryRequest(IOpcServiceRequestHeader, OpcReadHistoryDetails, HistoryReadValueId[])

C#

```
[CLSCompliant(false)]
public OpcReadNodesHistoryRequest(IOpcServiceRequestHeader header, OpcReadHistoryDetails details, params HistoryReadValueId[] commands)
```

Parameters

header [IOpcServiceRequestHeader](#)

details [OpcReadHistoryDetails](#)

commands [HistoryReadValueId\[\]](#)

Exceptions

[ArgumentNullException](#)

OpcReadNodesHistoryRequest(IOpcServiceRequestHeader, OpcReadHistoryDetails, IEnumerable<HistoryReadValueId>)

C#

```
[CLSCompliant(false)]
public OpcReadNodesHistoryRequest(IOpcServiceRequestHeader header, OpcReadHistoryDetails details, IEnumerable<HistoryReadValueId> commands)
```

Parameters

header [IOpcServiceRequestHeader](#)

details [OpcReadHistoryDetails](#)

commands [IEnumerable<HistoryReadValueId>](#)

Exceptions

[ArgumentNullException](#)

OpcReadNodesHistoryRequest(OpcReadHistoryDetails, HistoryReadValueId[])

C#

```
[CLSCompliant(false)]
public OpcReadNodesHistoryRequest(OpcReadHistoryDetails details, params HistoryReadValueId[]
commands)
```

Parameters

details [OpcReadHistoryDetails](#)

commands [HistoryReadValueId\[\]](#)

Exceptions

[ArgumentNullException](#)

OpcReadNodesHistoryRequest(OpcReadHistoryDetails, IEnumerable<HistoryReadValueId>)

C#

```
[CLSCompliant(false)]
public OpcReadNodesHistoryRequest(OpcReadHistoryDetails details,
IEnumerable<HistoryReadValueId> commands)
```

Parameters

details [OpcReadHistoryDetails](#)

commands [IEnumerable<HistoryReadValueId>](#)

Exceptions

[ArgumentNullException](#)

Properties

Details

C#

```
public OpcReadHistoryDetails Details { get; }
```

Property Value

[OpcReadHistoryDetails](#)

ReleaseContinuationPoints

C#

```
public bool ReleaseContinuationPoints { get; set; }
```

Property Value

[Boolean](#)

TimestampsToReturn

Gets or sets a value which specifies the timestamps to be returned for each requested [Value](#) attribute.

C#

```
public OpcTimestampsToReturn TimestampsToReturn { get; set; }
```

Property Value

[OpcTimestampsToReturn](#)

One of the members defined by the [OpcTimestampsToReturn](#) enumeration except [Neither](#).

Remarks

Using the value [Neither](#) as the timestamps to return is not valid and results into a response with the status code [BadInvalidTimestampArgument](#).

Table of Contents

Constructors	1
OpcReadNodesHistoryRequest(IOpcServiceRequestHeader, OpcReadHistoryDetails, HistoryReadValueId[])	1
OpcReadNodesHistoryRequest(IOpcServiceRequestHeader, OpcReadHistoryDetails, IEnumerable<HistoryReadValueId>)	1
OpcReadNodesHistoryRequest(OpcReadHistoryDetails, HistoryReadValueId[])	2
OpcReadNodesHistoryRequest(OpcReadHistoryDetails, IEnumerable<HistoryReadValueId>)	2
Properties	3
Details	3
ReleaseContinuationPoints	3
TimestampsToReturn	3

