

StatusChangedEventArgs Constructor

Initializes a new instance of the [StatusChangedEventArgs](#) class using the specified *source*, *exception* information.

Namespace: [Rfc1006LibNet.Advanced.EventArgs](#)

Assembly: Rfc1006LibNet.Advanced (in Rfc1006LibNet.Advanced.dll) Version: 1.0.2.0 (1.0.5.3)

Syntax

C#

```
public StatusChangedEventArgs(  
    Rfc1006Base source,  
    Exception exception,  
    Rfc1006Status oldStatus,  
    Rfc1006Status newStatus  
)
```

Parameters

source

Type: [Rfc1006LibNet.Advanced.Rfc1006Base](#)

Stores a reference to the object that raised the event.

exception

Type: [System.Exception](#)

Stores the error that occurred during the RFC1006 communication.

oldStatus

Type: [Rfc1006LibNet.Advanced.Rfc1006Status](#)

The old status of the connection.

newStatus

Type: [Rfc1006LibNet.Advanced.Rfc1006Status](#)

The new status of the connection.

See Also

Reference

[StatusChangedEventArgs Class](#)

[Rfc1006LibNet.Advanced.EventArgs Namespace](#)

Table of Contents

Syntax	1
Parameters	1
See Also	1
Reference	1