

StatusChangedEventArgs Class

Provides data for the [StatusChanged](#) event.

Inheritance Hierarchy

[System.Object](#)

[System.EventArgs](#)

[Rfc1006LibNet.Advanced.EventArgs.StatusChangedEventArgs](#)

Namespace: [Rfc1006LibNet.Advanced.EventArgs](#)

Assembly: Rfc1006LibNet.Advanced (in Rfc1006LibNet.Advanced.dll) Version: 1.0.2.0 (1.0.5.3)

Syntax

C#

```
public class StatusChangedEventArgs : EventArgs
```

The [StatusChangedEventArgs](#) type exposes the following members.

Constructors

--	Name	Description
	StatusChangedEventArgs	Initializes a new instance of the StatusChangedEventArgs class using the specified <i>source</i> , <i>exception</i> information.

[Top](#)

Properties

--	Name	Description
	Exception	Gets the error that was occurred during the RFC1006 communication.
	OriginalSource	Gets the original reporting source as determined by pure hit testing, before any possible Source adjustment by a parent class.
	PreviousStatus	Gets the previous status of the connection.
	Source	Gets or sets a reference to the object that raised the event.
	Status	Gets the actual status of the connection.

[Top](#)

See Also

Reference

[Rfc1006LibNet.Advanced.EventArgs Namespace](#)

Table of Contents

Inheritance Hierarchy	1
Syntax	1
Constructors	1
Properties	1
See Also	2
Reference	2

