

Rfc1006Client Constructor (Int32, String, Int32, Byte[], Byte[])

Initializes a new instance of the [Rfc1006Client](#) class using the specified *address*, *port*, *remoteTSAP*, *localTSAP* and *connectionTimeout* information and [DefaultAliveTime](#).

Namespace: [Rfc1006LibNet.Advanced](#)

Assembly: Rfc1006LibNet.Advanced (in Rfc1006LibNet.Advanced.dll) Version: 1.0.2.0 (1.0.5.3)

Syntax

C#

```

public Rfc1006Client(
    int connectionTimeout,
    string address,
    int port,
    byte[] remoteTSAP,
    byte[] localTSAP
)
    
```

Parameters

connectionTimeout

Type: [System.Int32](#)

The time in milliseconds after the connection will be closed

address

Type: [System.String](#)

To use to identifier the server IP.

port

Type: [System.Int32](#)

To use to identifier the server port

remoteTSAP

Type: [System.Byte\[\]](#)

To use to identifier the server TSAP.

localTSAP

Type: [System.Byte\[\]](#)

To use to identifier the client TSAP.

Exceptions

Exception	Condition
ArgumentNullException	The <i>address</i> is a null reference (Nothing in Visual Basic).
ArgumentOutOfRangeException	The is lower than zero.

See Also

Reference

[Rfc1006Client Class](#)

[Rfc1006Client Overload](#)

[Rfc1006LibNet.Advanced Namespace](#)

Table of Contents

Syntax	1
Parameters	1
Exceptions	1
See Also	2
Reference	2

