

Rfc1006Client Constructor (Int32, String, Int32, String, String, Int32)

Initializes a new instance of the [Rfc1006Client](#) class using the specified *address*, *remoteTSAP*, *connectionTimeout*, *localTSAP* and *aliveTime* information.

Namespace: [Rfc1006LibNet.Advanced](#)

Assembly: Rfc1006LibNet.Advanced (in Rfc1006LibNet.Advanced.dll) Version: 1.0.2.0 (1.0.5.3)

Syntax

C#

```
public Rfc1006Client(  
    int connectionTimeout,  
    string address,  
    int port,  
    string remoteTSAP,  
    string localTSAP,  
    int aliveTime  
)
```

Parameters

connectionTimeout

Type: [System.Int32](#)

The time in milliseconds after the connection will be closed

address

Type: [System.String](#)

To identifier the server IP.

port

Type: [System.Int32](#)

To use to identifier the server port

remoteTSAP

Type: [System.String](#)

To use to identifier the server TSAP.

localTSAP

Type: [System.String](#)

To use to identifier the client TSAP.

aliveTime

Type: [System.Int32](#)

The timeout in milliseconds

Exceptions

Exception	Condition
ArgumentNullException	The <i>address</i> is a null reference (Nothing in Visual Basic).
ArgumentOutOfRangeException	The <i>aliveTime</i> is lower than zero.
ArgumentOutOfRangeException	The is lower than zero.

See Also

Reference

[Rfc1006Client Class](#)

[Rfc1006Client Overload](#)

[Rfc1006LibNet.Advanced Namespace](#)

Table of Contents

Syntax	1
Parameters	1
Exceptions	2
See Also	2
Reference	2

