

Rfc1006Client Constructor (Int32, Rfc1006IPEndPoint)

Initializes a new instance of the [Rfc1006Client](#) class using the specified *endPoint* and *connectionTimeout* information.

Namespace: [Rfc1006LibNet.Advanced](#)

Assembly: Rfc1006LibNet.Advanced (in Rfc1006LibNet.Advanced.dll) Version: 1.0.2.0 (1.0.5.3)

Syntax

C#

```
public Rfc1006Client(
    int connectionTimeout,
    Rfc1006IPEndPoint endPoint
)
```

Parameters

connectionTimeout

Type: [System.Int32](#)

The time in milliseconds after the connection will be closed

endPoint

Type: [Rfc1006LibNet.Advanced.Rfc1006IPEndPoint](#)

The [Rfc1006IPEndPoint](#) class to use to identifier the server

Exceptions

Exception	Condition
ArgumentNullException	The <i>endPoint</i> is a null reference (Nothing in Visual Basic).
ArgumentOutOfRangeException	The is lower than zero.

See Also

Reference

[Rfc1006Client Class](#)

[Rfc1006Client Overload](#)

[Rfc1006LibNet.Advanced Namespace](#)

Table of Contents

Syntax	1
Parameters	1
Exceptions	1
See Also	1
Reference	1