







Rfc1006Client Constructor

Overload List

---	Name	Description
	Rfc1006Client(Rfc1006IPEndPoint)	Initializes a new instance of the Rfc1006Client class using the specified <i>endPoint</i> information.
	Rfc1006Client(Int32, Rfc1006IPEndPoint)	Initializes a new instance of the Rfc1006Client class using the specified <i>endPoint</i> and <i>connectionTimeout</i> information.
	Rfc1006Client(Rfc1006IPEndPoint, Int32)	Initializes a new instance of the Rfc1006Client class using the specified <i>endPoint</i> and <i>aliveTime</i> information.
	Rfc1006Client(Int32, Rfc1006IPEndPoint, Int32)	Initializes a new instance of the Rfc1006Client class using the specified <i>endPoint</i> , <i>connectionTimeout</i> and <i>aliveTime</i> information.
	Rfc1006Client(IPAddress, Byte[], Byte[])	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> and <i>localTSAP</i> information.
	Rfc1006Client(IPAddress, String, String)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> and <i>localTSAP</i> information.
	Rfc1006Client(String, Byte[], Byte[])	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> and <i>localTSAP</i> information.
	Rfc1006Client(String, String, String)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> and <i>localTSAP</i> information.
	Rfc1006Client(Int32, IPAddress, Byte[], Byte[])	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>localTSAP</i> and <i>connectionTimeout</i> information.
	Rfc1006Client(Int32, IPAddress, String, String)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>localTSAP</i> and <i>connectionTimeout</i> information.
	Rfc1006Client(Int32, String, String, String)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>localTSAP</i> and <i>connectionTimeout</i> information.
	Rfc1006Client(IPAddress, Byte[], Byte[], Int32)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>localTSAP</i> and <i>aliveTime</i> information.
	Rfc1006Client(IPAddress, Int32, Byte[], Byte[])	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> and <i>localTSAP</i> information.
	Rfc1006Client(IPAddress, Int32, String, String)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> and <i>localTSAP</i> information.
	Rfc1006Client(IPAddress, String, String, Int32)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>localTSAP</i> and <i>aliveTime</i> information.
	Rfc1006Client(String, Byte[], Byte[], Int32)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>localTSAP</i> and <i>aliveTime</i> information.

Name	Description
 Rfc1006Client(String, Int32, Byte[], Byte[])	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>port</i> , <i>remoteTSAP</i> and <i>localTSAP</i> information and DefaultConnectionTimeout .
 Rfc1006Client(String, Int32, String, String)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> and <i>localTSAP</i> information.
 Rfc1006Client(String, String, String, Int32)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>localTSAP</i> and <i>aliveTime</i> information.
 Rfc1006Client(Int32, IPAddress, Byte[], Byte[], Int32)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>connectionTimeout</i> , <i>localTSAP</i> and <i>aliveTime</i> information.
 Rfc1006Client(Int32, IPAddress, Int32, Byte[], Byte[])	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>localTSAP</i> and <i>connectionTimeout</i> information.
 Rfc1006Client(Int32, IPAddress, Int32, String, String)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>localTSAP</i> and <i>connectionTimeout</i> information.
 Rfc1006Client(Int32, IPAddress, String, String, Int32)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>connectionTimeout</i> , <i>localTSAP</i> and <i>aliveTime</i> information.
 Rfc1006Client(Int32, String, Byte[], Byte[], Int32)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>connectionTimeout</i> , <i>localTSAP</i> and <i>aliveTime</i> information.
 Rfc1006Client(Int32, String, Int32, Byte[], Byte[])	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>port</i> , <i>remoteTSAP</i> , <i>localTSAP</i> and <i>connectionTimeout</i> information and DefaultAliveTime .
 Rfc1006Client(Int32, String, Int32, String, String)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>localTSAP</i> and <i>connectionTimeout</i> information.
 Rfc1006Client(Int32, String, String, String, Int32)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>connectionTimeout</i> , <i>localTSAP</i> and <i>aliveTime</i> information.
 Rfc1006Client(IPAddress, Int32, Byte[], Byte[], Int32)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>localTSAP</i> and <i>aliveTime</i> information.
 Rfc1006Client(IPAddress, Int32, String, String, Int32)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>localTSAP</i> and <i>aliveTime</i> information.
 Rfc1006Client(String, Int32, Byte[], Byte[], Int32)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>port</i> , <i>remoteTSAP</i> , <i>localTSAP</i> and <i>aliveTime</i> information and DefaultAliveTime .
 Rfc1006Client(String, Int32, String, String, Int32)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>localTSAP</i> and <i>aliveTime</i> information.
 Rfc1006Client(Int32, IPAddress, Int32, Byte[], Byte[], Int32)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>connectionTimeout</i> , <i>localTSAP</i> and <i>aliveTime</i> information.
 Rfc1006Client(Int32, IPAddress, Int32, String, String, Int32)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>connectionTimeout</i> , <i>localTSAP</i> and <i>aliveTime</i> information.

--	Name	Description
	Rfc1006Client(Int32, String, Int32, Byte[], Byte[], Int32)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>port</i> , <i>remoteTSAP</i> , <i>connectionTimeout</i> , <i>localTSAP</i> and <i>aliveTime</i> information and DefaultAliveTime .
	Rfc1006Client(Int32, String, Int32, String, String, Int32)	Initializes a new instance of the Rfc1006Client class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>connectionTimeout</i> , <i>localTSAP</i> and <i>aliveTime</i> information.

[Top](#)

See Also

Reference

[Rfc1006Client Class](#)

[Rfc1006LibNet.Advanced Namespace](#)

Table of Contents

Overload List	1
See Also	3
Reference	3