

# Rfc1006Server Constructor

## Overload List

| --- | Name                                                             | Description                                                                                                                                                                        |
|-----|------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ✖   | <a href="#">Rfc1006Server(Rfc1006IPEndPoint)</a>                 | Initializes a new instance of the <a href="#">Rfc1006Server</a> class using the specified <i>endPoint</i> information.                                                             |
| ✖   | <a href="#">Rfc1006Server(Byte[], Byte[])</a>                    | Initializes a new instance of the <a href="#">Rfc1006Server</a> class using the specified <i>remoteTSAP</i> and <i>localTSAP</i> information.                                      |
| ✖   | <a href="#">Rfc1006Server(String, String)</a>                    | Initializes a new instance of the <a href="#">Rfc1006Server</a> class using the specified <i>remoteTSAP</i> and <i>localTSAP</i> information.                                      |
| ✖   | <a href="#">Rfc1006Server(Rfc1006IPEndPoint, Int32)</a>          | Initializes a new instance of the <a href="#">Rfc1006Server</a> class using the specified <i>endPoint</i> information.                                                             |
| ✖   | <a href="#">Rfc1006Server(Byte[], Byte[], Int32)</a>             | Initializes a new instance of the <a href="#">Rfc1006Server</a> class using the specified <i>remoteTSAP</i> , and <i>localTSAP</i> and <i>aliveTime</i> information.               |
| ✖   | <a href="#">Rfc1006Server(IPAddress, Byte[], Byte[])</a>         | Initializes a new instance of the <a href="#">Rfc1006Server</a> class using the specified <i>address</i> , <i>remoteTSAP</i> and <i>localTSAP</i> information.                     |
| ✖   | <a href="#">Rfc1006Server(IPAddress, String, String)</a>         | Initializes a new instance of the <a href="#">Rfc1006Server</a> class using the specified <i>address</i> , <i>remoteTSAP</i> and <i>localTSAP</i> information.                     |
| ✖   | <a href="#">Rfc1006Server(IPEndPoint, Byte[], Byte[])</a>        | Initializes a new instance of the <a href="#">Rfc1006Server</a> class using the specified <i>endPoint</i> , <i>remoteTSAP</i> and <i>localTSAP</i> information.                    |
| ✖   | <a href="#">Rfc1006Server(String, Byte[], Byte[])</a>            | Initializes a new instance of the <a href="#">Rfc1006Server</a> class using the specified <i>address</i> , <i>remoteTSAP</i> and <i>localTSAP</i> information.                     |
| ✖   | <a href="#">Rfc1006Server(String, String, Int32)</a>             | Initializes a new instance of the <a href="#">Rfc1006Server</a> class using the specified <i>remoteTSAP</i> , <i>localTSAP</i> and <i>aliveTime</i> information.                   |
| ✖   | <a href="#">Rfc1006Server(String, String, String)</a>            | Initializes a new instance of the <a href="#">Rfc1006Server</a> class using the specified <i>address</i> , <i>remoteTSAP</i> and <i>localTSAP</i> information.                     |
| ✖   | <a href="#">Rfc1006Server(IPAddress, Byte[], Byte[], Int32)</a>  | Initializes a new instance of the <a href="#">Rfc1006Server</a> class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>localTSAP</i> and <i>aliveTime</i> information.  |
| ✖   | <a href="#">Rfc1006Server(IPAddress, String, String, Int32)</a>  | Initializes a new instance of the <a href="#">Rfc1006Server</a> class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>localTSAP</i> and <i>aliveTime</i> information.  |
| ✖   | <a href="#">Rfc1006Server(IPEndPoint, Byte[], Byte[], Int32)</a> | Initializes a new instance of the <a href="#">Rfc1006Server</a> class using the specified <i>endPoint</i> , <i>remoteTSAP</i> , <i>localTSAP</i> and <i>aliveTime</i> information. |
| ✖   | <a href="#">Rfc1006Server(String, Byte[], Byte[], Int32)</a>     | Initializes a new instance of the <a href="#">Rfc1006Server</a> class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>localTSAP</i> and <i>aliveTime</i> information.  |
| ✖   | <a href="#">Rfc1006Server(String, String, String, Int32)</a>     | Initializes a new instance of the <a href="#">Rfc1006Server</a> class using the specified <i>address</i> , <i>remoteTSAP</i> , <i>localTSAP</i> and <i>aliveTime</i> information.  |

---

[Top](#)

## See Also

### Reference

[Rfc1006Server Class](#)

[Rfc1006LibNet.Advanced Namespace](#)

# Table of Contents

|                      |   |
|----------------------|---|
| <b>Overload List</b> | 1 |
| <b>See Also</b>      | 2 |
| Reference            | 2 |

