

PlcDeviceConnectionStateChangedEventArgs Members

Namespace: IPS7Lnk.Advanced

Assemblies: IPS7LnkNet.Advanced.dll, IPS7LnkNet.Advanced.dll

The [PlcDeviceConnectionStateChangedEventArgs](#) type exposes the following members.

Constructors

PlcDeviceConnectionStateChangedEventArgs(PlcDeviceConnectionState, PlcDeviceConnectionState)

Initializes a new instance of the [PlcDeviceConnectionStateChangedEventArgs](#) class using the specified **oldState** and **newState**.

C#

```
public PlcDeviceConnectionStateChangedEventArgs(PlcDeviceConnectionState oldState,
PlcDeviceConnectionState newState)
```

Parameters

oldState [PlcDeviceConnectionState](#)

The state before the change.

newState [PlcDeviceConnectionState](#)

The state after the change.

Properties

NewState

Gets the state after the change.

C#

```
public PlcDeviceConnectionState NewState { get; }
```

Property Value

[PlcDeviceConnectionState](#)

The [PlcDeviceConnectionState](#) after the change.

OldState

Gets the state before the change.

C#

```
public PlcDeviceConnectionState OldState { get; }
```

Property Value

[PlcDeviceConnectionState](#)

The [PlcDeviceConnectionState](#) before the change.

Table of Contents

| | |
|---|---|
| Constructors | 1 |
| PlcDeviceConnectionStateChangedEventArgs(PlcDeviceConnectionState, PlcDeviceConnectionState) | 1 |
| Properties | 1 |
| NewState | 1 |
| OldState | 2 |

