

PlcLReal Class

Namespace: IPS7Lnk.Advanced

Assemblies: IPS7LnkNet.Advanced.dll

Represents a [Double](#) value (in PLC a LREAL) its value defines a double-precision floating-point number.

C#

```
public class PlcLReal : PlcValue<double>, IPlcValue<double>, IPlcValue, IPlcSymbol,
IPlcEntity, IPlcStatusProvider, IPlcRelocatable<IPlcValue>, IPlcRelocatable,
ISupportInitialize
```

Inheritance [Object](#) > [PlcValue<Double>](#) > [PlcLReal](#)

Implements [IPlcValue<Double>](#), [IPlcValue](#), [IPlcSymbol](#), [IPlcEntity](#), [IPlcStatusProvider](#),
[IPlcRelocatable<IPlcValue>](#), [IPlcRelocatable](#), [ISupportInitialize](#)

Remarks

While a PLC value of this type represents a [Double](#) value, all PLC operations performed using this class are done using the [LWord](#). A PLC developer knows a value of this type as LREAL.

Constructors

Name	Description
PlcLReal(PlcIdentity)	Initializes a new instance of the PlcLReal class using the specified identity
PlcLReal(PlcIdentity, Double)	Initializes a new instance of the PlcLReal class using the specified identity and value .
PlcLReal(PlcIdentity, PlcName)	Initializes a new instance of the PlcLReal class using the specified identity and name .
PlcLReal(PlcIdentity, PlcName, Double)	Initializes a new instance of the PlcLReal class using the specified identity , name and value .
PlcLReal(PlcLRealType)	Initializes a new instance of the PlcLReal class using the specified type
PlcLReal(PlcLRealType, Double)	Initializes a new instance of the PlcLReal class using the specified type and value .
PlcLReal(PlcLRealType, PlcName)	Initializes a new instance of the PlcLReal class using the specified type and name .
PlcLReal(PlcLRealType, PlcName, Double)	Initializes a new instance of the PlcLReal class using the specified type , name and value .

Methods

Name	Description
GetValueCore(PlcDeviceConnection)	Retrieves the current value of the PLC value from a IPlcDevice using the connection specified.

Name	Description
<code>RelocateCore(PlcAddress)</code>	Relocates the value to the address specified.
<code>SetValueCore(PlcDeviceConnection, Double)</code>	Stores the value in the IPlcDevice assigned to the connection specified.

Table of Contents

Remarks	1
Constructors	1
Methods	1

