

PlcRawTypes Members

Namespace: IPS7Lnk.Advanced

Assemblies: IPS7LnkNet.Advanced.dll, IPS7LnkNet.Advanced.dll

The [PlcRawTypes](#) type exposes the following members.

Fields

Bit

Specifies the string representation of the bit raw type.

C#

```
public const string Bit = "X"
```

Field Value

String

Byte

Specifies the string representation of the byte raw type.

C#

```
public const string Byte = "B"
```

Field Value

String

DWord

Specifies the string representation of the double word raw type.

C#

```
public const string DWord = "D"
```

Field Value

String

Word

Specifies the string representation of the word raw type.

C#

```
public const string Word = "W"
```

Field Value

String

Methods

GetChar(PlcRawType)

Retrieves the according character representation which matches the specified `value`.

C#

```
public static char GetChar(PlcRawType value)
```

Parameters

`value` PlcRawType

The `PlcRawType` its character representation is to be retrieved.

Returns

Char

The character representation of the `value` specified.

Exceptions

`ArgumentException`

The according character representation could not be retrieved.

GetRawType(Char)

Retrieves the according `PlcRawType` value which matches the specified `value`.

C#

```
public static PlcRawType GetRawType(char value)
```

Parameters

`value` Char

The character representation of the `PlcRawType` to retrieve.

Returns

PlcRawType

The according [PlcRawType](#) value of the `value` specified.

Exceptions

ArgumentException

The according [PlcRawType](#) could not be retrieved.

GetRawType(String)

Retrieves the according [PlcRawType](#) value which matches the specified `value`.

C#

```
public static PlcRawType GetRawType(string value)
```

Parameters

`value` String

The string representation of the [PlcRawType](#) to retrieve.

Returns

PlcRawType

The according [PlcRawType](#) value of the `value` specified.

Exceptions

ArgumentException

The `value` is equal to `Empty` or the according [PlcRawType](#) could not be retrieved.

ArgumentNullException

The `value` is a null reference (Nothing in Visual Basic).

GetSize(PlcRawType)

Retrieves the according size in bytes of the specified `value`.

C#

```
public static int GetSize(PlcRawType value)
```

Parameters

`value` `PlcRawType`

The `PlcRawType` its size is to be retrieved.

Returns

`Int32`

The according size (in bytes) of the `value` specified.

Exceptions

`ArgumentException`

The according size could not be retrieved.

GetSize(PlcRawType, Boolean)

Retrieves the according size (optionally in bytes or bits) of the specified `value`.

C#

```
public static int GetSize(PlcRawType value, bool inBytes)
```

Parameters

`value` `PlcRawType`

The `PlcRawType` its size is to be retrieved.

`inBytes` `Boolean`

The value true, to retrieve the size of `value` in bytes; otherwise the value false to retrieve the size in bits.

Returns

`Int32`

The according size either in bytes or in bits of the `value` specified.

Exceptions

`ArgumentException`

The according size could not be retrieved.

GetString(PlcRawType)

Retrieves the according string representation which matches the specified **value**.

C#

```
public static string GetString(PlcRawType value)
```

Parameters

value [PlcRawType](#)

The [PlcRawType](#) its string representation is to be retrieved.

Returns

[String](#)

The string representation of the **value**.

Exceptions

[ArgumentException](#)

The according string representation could not be retrieved.

Table of Contents

Fields	1
Bit	1
Byte	1
DWord	1
Word	1
Methods	2
GetChar(PlcRawType)	2
GetRawType(Char)	2
GetRawType(String)	3
GetSize(PlcRawType)	3
GetSize(PlcRawType, Boolean)	4
GetString(PlcRawType)	5