

# PlcS5Time Class

**Namespace:** IPS7Lnk.Advanced

**Assemblies:** IPS7LnkNet.Advanced.dll

Represents a [TimeSpan](#) value (in PLC a S5TIME) its value defines an time interval.

**C#**

```
public class PlcS5Time : PlcValue<TimeSpan>, IPlcValue<TimeSpan>, IPlcValue, IPlcSymbol,
IPlcEntity, IPlcStatusProvider, IPlcRelocatable<IPlcValue>, IPlcRelocatable,
ISupportInitialize
```

**Inheritance** [Object](#) > [PlcValue<TimeSpan>](#) > [PlcS5Time](#)

**Implements** [IPlcValue<TimeSpan>](#), [IPlcValue](#), [IPlcSymbol](#), [IPlcEntity](#), [IPlcStatusProvider](#), [IPlcRelocatable<IPlcValue>](#), [IPlcRelocatable](#), [ISupportInitialize](#)

## Remarks

While a PLC value of this type represents a [TimeSpan](#) value, all PLC operations performed using this class are done using the [Word](#). A PLC developer knows a value of this type as S5TIME.

## Constructors

Name	Description
<a href="#">PlcS5Time(PlcIdentity)</a>	Initializes a new instance of the <a href="#">PlcS5Time</a> class using the specified <a href="#">identity</a>
<a href="#">PlcS5Time(PlcIdentity, PlcName)</a>	Initializes a new instance of the <a href="#">PlcS5Time</a> class using the specified <a href="#">identity</a> and <a href="#">name</a> .
<a href="#">PlcS5Time(PlcIdentity, PlcName, TimeSpan)</a>	Initializes a new instance of the <a href="#">PlcS5Time</a> class using the specified <a href="#">identity</a> , <a href="#">name</a> and <a href="#">value</a> .
<a href="#">PlcS5Time(PlcIdentity, TimeSpan)</a>	Initializes a new instance of the <a href="#">PlcS5Time</a> class using the specified <a href="#">identity</a> and <a href="#">value</a> .
<a href="#">PlcS5Time(PlcS5TimeType)</a>	Initializes a new instance of the <a href="#">PlcS5Time</a> class using the specified <a href="#">type</a>
<a href="#">PlcS5Time(PlcS5TimeType, PlcName)</a>	Initializes a new instance of the <a href="#">PlcS5Time</a> class using the specified <a href="#">type</a> and <a href="#">name</a> .
<a href="#">PlcS5Time(PlcS5TimeType, PlcName, TimeSpan)</a>	Initializes a new instance of the <a href="#">PlcS5Time</a> class using the specified <a href="#">type</a> , <a href="#">name</a> and <a href="#">value</a> .
<a href="#">PlcS5Time(PlcS5TimeType, TimeSpan)</a>	Initializes a new instance of the <a href="#">PlcS5Time</a> class using the specified <a href="#">type</a> and <a href="#">value</a> .

## Fields

Name	Description
<a href="#">MaxValue</a>	Represents the largest possible value of a <a href="#">PlcS5Time</a> .
<a href="#">MinValue</a>	Represents the smallest possible value of a <a href="#">PlcS5Time</a> .

# Properties

Name	Description
Origin	Gets a value of the <a href="#">PlcS5TimeOrigin</a> enumeration which indicate which origin the <a href="#">PlcS5Time</a> does use to represent the <a href="#">TimeSpan</a> which is provided by the <a href="#">Value</a> property.
Value	Gets or sets the value assigned to the PLC value.

# Methods

Name	Description
<a href="#">GetValueCore</a> ( <a href="#">PlcDeviceConnection</a> )	Retrieves the current value of the PLC value from a <a href="#">IPlcDevice</a> using the <a href="#">connection</a> specified.
<a href="#">IsValidValue</a> ( <a href="#">Object</a> )	Determines whether the provided value is accepted for the type of PLC value through basic type checking and also potentially if it is within the allowed range of value for that type.
<a href="#">RelocateCore</a> ( <a href="#">PlcAddress</a> )	Relocates the value to the <a href="#">address</a> specified.
<a href="#">SetValueCore</a> ( <a href="#">PlcDeviceConnection</a> , <a href="#">TimeSpan</a> )	Stores the <a href="#">value</a> in the <a href="#">IPlcDevice</a> assigned to the <a href="#">connection</a> specified.

# Table of Contents

Remarks .....	1
<b>Constructors</b> .....	1
<b>Fields</b> .....	1
<b>Properties</b> .....	2
<b>Methods</b> .....	2

